NUROIL TRADING
Sharjah, United Arab Emirates

Ethyl Acetate

CHCOOCH | Solvent, 99.5% min

PRODUCT OVERVIEW

Fast-evaporating solvent for printing inks, coatings, adhesives, pharmaceuticals and extraction. Highly flammable: keep from ignition sources, earth containers and work with good ventilation.

TYPICAL SPECIFICATION

Characteristic	Units	Typical value	Test method
Purity	-	**99.5% min (99.8% typical)**	Gas chromatography
Water	-	**0.05–0.1% max**	Karl Fischer
Acidity (as acetic acid)	-	**0.005–0.01% max**	Titration
Ethanol	-	**0.1–0.2% max**	Gas chromatography
Colour	-	**10 Pt-Co (APHA) max**	ASTM D1209
Residue on evaporation	-	**0.005% max**	Gravimetric
Density at 20 °C	-	**0.897–0.902 g/cm³**	ASTM D4052
Distillation range	-	**Within about 76–78 °C**	ASTM D1078
Appearance	-	**Clear, colourless liquid, free of suspended matter**	Visual

SUPPLY AND PACKING

UN-approved steel drums, IBCs and ISO tanks, shipped as class 3 dangerous goods (UN 1173, PG II). FOB, CFR and CIF on request; pack sizes and loads are confirmed with each offer.

DOCUMENTATION

Every shipment includes a Certificate of Analysis. Certificate of Origin and MSDS are available on request. Destination-specific import or phytosanitary documentation is confirmed where applicable.

NOTICE

Values are typical and published for reference; they are not a certificate of analysis. Agree the specification of the offered batch, the packing and any destination requirements before ordering.