Pool Flocculant

Aluminium-based or polymer | Liquid flocculant, typical formulations

PRODUCT OVERVIEW

Liquid pool flocculant that binds fine particles into floc which settles to the floor for vacuuming to waste. Formulations differ; the offered product's TDS and SDS give its exact composition. Aluminium-based grades are acidic and can cause serious eye damage: wear eye protection.

TYPICAL SPECIFICATION

Characteristic	Units	Typical value	Test method
Base	-	**Polyaluminium chloride or aluminium sulphate solution, often with a cationic polymer, per TDS**	Producer formulation
Aluminium (as AlO), aluminium-based	-	**Typically about 5–18%, by formulation**	EDTA titration
pH (as supplied)	-	**About 2.5–4.5**	pH meter
Density at 20 °C	-	**About 1.1–1.35 g/cm³**	Hydrometer
Appearance	-	**Clear to slightly hazy, colourless to pale yellow liquid**	Visual

SUPPLY AND PACKING

HDPE cans of 1 to 25 litres, 200-litre drums and 1,000-litre IBCs; transport class per the product SDS. FOB, CFR and CIF on request; pack sizes, formulation and loads are confirmed with each offer.

DOCUMENTATION

Every shipment includes a Certificate of Analysis. Certificate of Origin and MSDS are available on request. Destination-specific import or phytosanitary documentation is confirmed where applicable.

NOTICE

Values are typical and published for reference; they are not a certificate of analysis. Agree the specification of the offered batch, the packing and any destination requirements before ordering.