Granular Sulphur

Elemental sulphur | Granular form

PRODUCT OVERVIEW

Uniform, low-dust 2.4 to 4.4 mm pellets, the international trade standard for sulphuric acid production and bulk shipment.

TYPICAL SPECIFICATION

Characteristic	Units	Typical value	Test method
Sulphur content	-	**99.5% min**	ASTM D4239
Ash	-	**0.05% max**	ASTM D4239
Moisture	-	**0.5% max**	ASTM D2790
Acidity as HSO	-	**0.05% max**	Titration
Carbon	-	**0.05% max**	ASTM D4239
Particle size	-	**2.4 to 4.4 mm**	Sieve analysis
Dust generation	-	**Low**	-
Colour	-	**Bright yellow**	Visual
Appearance	-	**Uniform rounded granules**	Visual

SUPPLY AND PACKING

Dust- and moisture-resistant PP/PE jumbo bags (FIBC) and bulk cargo, depending on form and shipment. FOB is quoted from Jebel Ali, Port Khalid and Sharjah Hamriyah; CFR and CIF are available on request. Origin and availability are confirmed at the enquiry stage.

DOCUMENTATION

A Certificate of Analysis is supplied with every shipment. Certificate of Origin and Safety Data Sheet are available on request.

NOTICE

Values are typical and published for reference; they are not a certificate of analysis. Agree the specification of the offered batch, the packing and any destination requirements before ordering.