Sulphur Lump

Elemental sulphur | Lump form

PRODUCT OVERVIEW

Irregular solid sulphur pieces, typically 99.5 to 99.8% purity, for facilities with on-site crushing or melting.

TYPICAL SPECIFICATION

Characteristic	Units	Typical value	Test method
Sulphur (S) content	-	**99.5 to 99.8%**	ASTM D4239
Ash content	-	**0.05% max**	ASTM D4239
Moisture	-	**1.0% max**	ASTM D2790
Acidity (as HSO)	-	**0.05% max**	Titration
Carbon content	-	**0.10% max**	ASTM D4239
Particle size	-	**Irregular, unsized**	-
Dust generation	-	**Higher**	-
Colour	-	**Yellow**	Visual
Appearance	-	**Irregular solid pieces**	Visual

SUPPLY AND PACKING

Dust- and moisture-resistant PP/PE jumbo bags (FIBC) and bulk cargo, depending on form and shipment. FOB is quoted from Jebel Ali, Port Khalid and Sharjah Hamriyah; CFR and CIF are available on request. Origin and availability are confirmed at the enquiry stage.

DOCUMENTATION

A Certificate of Analysis is supplied with every shipment. Certificate of Origin and Safety Data Sheet are available on request.

NOTICE

Values are typical and published for reference; they are not a certificate of analysis. Agree the specification of the offered batch, the packing and any destination requirements before ordering.