Pastillated Sulphur

Elemental sulphur | Pastillated form

PRODUCT OVERVIEW

Precision drop-formed hemispherical pastilles with very consistent geometry, for uniform dosing and low-dust systems.

TYPICAL SPECIFICATION

Characteristic	Units	Typical value	Test method
Sulphur content	-	**99.5% min**	ASTM D4239
Ash	-	**0.05% max**	ASTM D4239
Moisture	-	**0.2% max**	ASTM D2790
Acidity as HSO	-	**0.05% max**	Titration
Carbon	-	**0.05% max**	ASTM D4239
Particle size	-	**Uniform hemispherical, 2 to 5 mm**	Sieve / dimensional check
Dust generation	-	**Very low**	-
Colour	-	**Bright yellow**	Visual
Appearance	-	**Uniform hemispherical pastilles**	Visual

SUPPLY AND PACKING

Dust- and moisture-resistant PP/PE jumbo bags (FIBC) and bulk cargo, depending on form and shipment. FOB is quoted from Jebel Ali, Port Khalid and Sharjah Hamriyah; CFR and CIF are available on request. Origin and availability are confirmed at the enquiry stage.

DOCUMENTATION

A Certificate of Analysis is supplied with every shipment. Certificate of Origin and Safety Data Sheet are available on request.

NOTICE

Values are typical and published for reference; they are not a certificate of analysis. Agree the specification of the offered batch, the packing and any destination requirements before ordering.